

1995 1996 1997 1998 1999 2000 2001 2002 2003 2004 2005 2006 2007 2008 2009 2010 2011 2012 2013 2014 2015 2016 2017 2018 2019 2020 2021 2022 2023 2024 2025 2026 2027 2028 2029 2030 2031 2032 2033 2034 2035 2036 2037 2038 2039 2040 2041 2042 2043 2044 2045 2046 2047 2048 2049 2050 2051 2052 2053 2054 2055 2056 2057 2058 2059 2060 2061 2062 2063 2064 2065 2066 2067 2068 2069 2070 2071 2072 2073 2074 2075 2076 2077 2078 2079 2080 2081 2082 2083 2084 2085 2086 2087 2088 2089 2090 2091 2092 2093 2094 2095 2096 2097 2098 2099 2100 2101 2102 2103 2104 2105 2106 2107 2108 2109 2110 2111 2112 2113 2114 2115 2116 2117 2118 2119 2120 2121 2122 2123 2124 2125 2126 2127 2128 2129 2130 2131 2132 2133 2134 2135 2136 2137 2138 2139 2140 2141 2142 2143 2144 2145 2146 2147 2148 2149 2150 2151 2152 2153 2154 2155 2156 2157 2158 2159 2160 2161 2162 2163 2164 2165 2166 2167 2168 2169 2170 2171 2172 2173 2174 2175 2176 2177 2178 2179 2180 2181 2182 2183 2184 2185 2186 2187 2188 2189 2190 2191 2192 2193 2194 2195 2196 2197 2198 2199 2200 2201 2202 2203 2204 2205 2206 2207 2208 2209 2210 2211 2212 2213 2214 2215 2216 2217 2218 2219 2220 2221 2222 2223 2224 2225 2226 2227 2228 2229 2230 2231 2232 2233 2234 2235 2236 2237 2238 2239 2240 2241 2242 2243 2244 2245 2246 2247 2248 2249 2250 2251 2252 2253 2254 2255 2256 2257 2258 2259 2260 2261 2262 2263 2264 2265 2266 2267 2268 2269 2270 2271 2272 2273 2274 2275 2276 2277 2278 2279 2280 2281 2282 2283 2284 2285 2286 2287 2288 2289 2290 2291 2292 2293 2294 2295 2296 2297 2298 2299 2300 2301 2302 2303 2304 2305 2306 2307 2308 2309 2310 2311 2312 2313 2314 2315 2316 2317 2318 2319 2320 2321 2322 2323 2324 2325 2326 2327 2328 2329 2330 2331 2332 2333 2334 2335 2336 2337 2338 2339 2340 2341 2342 2343 2344 2345 2346 2347 2348 2349 2350 2351 2352 2353 2354 2355 2356 2357 2358 2359 2360 2361 2362 2363 2364 2365 2366 2367 2368 2369 2370 2371 2372 2373 2374 2375 2376 2377 2378 2379 2380 2381 2382 2383 2384 2385 2386 2387 2388 2389 2390 2391 2392 2393 2394 2395 2396 2397 2398 2399 2400 2401 2402 2403 2404 2405 2406 2407 2408 2409 2410 2411 2412 2413 2414 2415 2416 2417 2418 2419 2420 2421 2422 2423 2424 2425 2426 2427 2428 2429 2430 2431 2432 2433 2434 2435 2436 2437 2438 2439 2440 2441 2442 2443 2444 2445 2446 2447 2448 2449 2450 2451 2452 2453 2454 2455 2456 2457 2458 2459 2460 2461 2462 2463 2464 2465 2466 2467 2468 2469 2470 2471 2472 2473 2474 2475 2476 2477 2478 2479 2480 2481 2482 2483 2484 2485 2486 2487 2488 2489 2490 2491 2492 2493 2494 2495 2496 2497 2498 2499 2500 2501 2502 2503 2504 2505 2506 2507 2508 2509 2510 2511 2512 2513 2514 2515 2516 2517 2518 2519 2520 2521 2522 2523 2524 2525 2526 2527 2528 2529 2530 2531 2532 2533 2534 2535 2536 2537 2538 2539 2540 2541 2542 2543 2544 2545 2546 2547 2548 2549 2550 2551 2552 2553 2554 2555 2556 2557 2558 2559 2560 2561 2562 2563 2564 2565 2566 2567 2568 2569 2570 2571 2572 2573 2574 2575 2576 2577 2578 2579 2580 2581 2582 2583 2584 2585 2586 2587 2588 2589 2590 2591 2592 2593 2594 2595 2596 2597 2598 2599 2600 2601 2602 2603 2604 2605 2606 2607 2608 2609 2610 2611 2612 2613 2614 2615 2616 2617 2618 2619 2620 2621 2622 2623 2624 2625 2626 2627 2628 2629 2630 2631 2632 2633 2634 2635 2636 2637 2638 2639 2640 2641 2642 2643 2644 2645 2646 2647 2648 2649 2650 2651 2652 2653 2654 2655 2656 2657 2658 2659 2660 2661 2662 2663 2664 2665 2666 2667 2668 2669 2670 2671 2672 2673 2674 2675 2676 2677 2678 2679 2680 2681 2682 2683 2684 2685 2686 2687 2688 2689 2690 2691 2692 2693 2694 2695 2696 2697 2698 2699 2700 2701 2702 2703 2704 2705 2706 2707 2708 2709 2710 2711 2712 2713 2714 2715 2716 2717 2718 2719 2720 2721 2722 2723 2724 2725 2726 2727 2728 2729 2730 2731 2732 2733 2734 2735 2736 2737 2738 2739 2740 2741 2742 2743 2744 2745 2746 2747 2748 2749 2750 2751 2752 2753 2754 2755 2756 2757 2758 2759 2760 2761 2762 2763 2764 2765 2766 2767 2768 2769 2770 2771 2772 2773 2774 2775 2776 2777 2778 2779 2780 2781 2782 2783 2784 2785 2786 2787 2788 2789 2790 2791 2792 2793 2794 2795 2796 2797 2798 2799 2800 2801 2802 2803 2804 2805 2806 2807 2808 2809 2810 2811 2812 2

TITLE:	CIGARETTE PACKAGE HAVING A CIGARETTE SAVER
INVENTOR:	WILLIAM ROBERT COLLETT TIMOTHY FREDERICK THOMAS
ASSIGNEE:	R. J. Reynolds Tobacco Company Winston-Salem, North Carolina

Date of Deposit March 20, 2001

Parthenia S. Galloway
(Typed or printed name of person mailing
paper or fee)

Grover M. Myers, Esquire
Reg. No. 25,359
R. J. Reynolds Tobacco Company
P.O. Box 1487
Winston-Salem, NC 27102-1487
Tel: 336/741-2694

CIGARETTE PACKAGE HAVING A CIGARETTE SAVER

Field of the Invention

The present invention relates to a cigarette saver and to a package of smoking articles, such as cigarettes, having a cigarette saver.

5

Background of the Invention

Smoking articles, such as cigarettes, conventionally have been sold in packages. Typically, each package contains about twenty or about twenty-five cigarettes.

10

One type of popular cigarette package is the so-called "hard pack," "crush proof box" or "hinged lid package." Such a package has a generally cuboid-type shape, is manufactured from resilient paperboard, and includes an outer wrap of transparent polypropylene film. Hinged lid cigarette packages conventionally are made from two paperboard blanks. One blank forms the body and lid of the package.

15

The second blank forms an insert or inner frame which is assembled to the inside of the front and side walls of the package. The inner frame projects above the front and side walls of the package body, and provides a seal between the lid and body when the package is closed. See, for example, U.S. Pat. No. 4,852,734 to Allen et al. Other types of designs of blanks for hinged lid cigarette packages can be of the type

20

described in U.S. Pat. Nos. 3,874,581 to Fox et al., 3,944,066 to Niepmann, and 5,139,140 to Burrows et al.

Cigarettes also can be packaged in a container having the form of a so-called "soft pack." See, for example, U.S. Pat. Nos. 3,695,422 to Tripodi and 4,717,017 to

Sprinke, Jr., et al. Cigarettes are removed from a soft package by tearing away a portion of the top of the package, in order that cigarettes can be easily accessed from the top of the package.

In the past, cigarette packages have been designed that can extinguish lighted cigarettes. For example, U.S. Patent No. 3,096,878 to Whitley et al. relates to a tobacco package with a built in ashtray. Other cigarette packages allow for lighted cigarettes to be extinguished and for the cigarette butts to be stored. See, for example, U.S. Patent Nos. 3,159,272 to Swift, 4,207,976 to Herman, and 5,992,621 to Grant et al. However, the cigarette packages disclosed in these patents have a more complex construction and design than conventional cigarette packages. For example, both Swift and Grant et al. involve individual compartments for each cigarette. Packages such as these would be difficult to integrate into an automated cigarette manufacturing and packaging process.

Cigarette prices have increased and the number of places that a smoker can enjoy a cigarette has decreased. Therefore, there is an increased need for saving cigarettes that have not been completely consumed for later use. It would also be desirable to have a cigarette package that allows for the extinguishing and storing of cigarettes that resembles conventional cigarette packages and that is easily integrated into a cigarette manufacturing and packaging process.

Summary of the Invention

The present invention relates to a cigarette saver. As used herein, the term "cigarette saver" refers generally to a device for extinguishing a burning cigarette and

storing it so that the smoker can relight the extinguished cigarette and smoke it later. Thus, if a person must extinguish a cigarette before they have finished smoking it, the person can extinguish and store the cigarette in a cigarette saver of the present invention. When the person has an opportunity to resume smoking the cigarette, the person may remove the extinguished cigarette from the cigarette saver and relight it.

An embodiment of a cigarette saver of the present invention comprises a device having two ends, wherein the first end includes an opening to a channel. The size of the opening is greater than the diameter of the cigarettes. In one embodiment where the opening is circular, the diameter may be just slightly larger than the diameter of the cigarettes such that a minimal amount of air enters the channel when a person extinguishes a cigarette. In another embodiment, the opening is an oval (i.e., elliptical) that is larger than the diameter of the cigarettes. In this embodiment, the elliptical opening narrows to a generally cylindrical extinguishing portion of the channel. The length of the channel is preferably less than the length of the cigarettes such that the extinguished cigarette may be easily removed from the cigarette saver. The channel also terminates in the cigarette saver (i.e., does not extend through a second end of the device). The end of the channel may be tapered to assist in extinguishing the cigarette.

The cigarette saver may be constructed from various materials known in the art, such as plastic and metal. The cigarette saver may be a variety of shapes. In one embodiment, the cigarette saver may be a substantially rectangular body surrounding the cylindrical channel. In another embodiment, the device may be a tube or cylinder.

In another embodiment, a cigarette saver comprises a substantially rectangular body having two end portions and including a cylindrical channel being open at a first end portion of the substantially rectangular body and terminating in the substantially rectangular body. Another embodiment of a cigarette saver comprises a body having
5 two end portions and including a bore open at one end portion of the body.

The present invention also relates to a cigarette package. An embodiment of a cigarette package of the present invention comprises a crush proof box (i.e., a hard pack or a hinged lid package), a plurality of cigarettes and a cigarette saver. In one embodiment, the cigarette package comprises twenty cigarettes. The cigarette saver
10 may be any of the embodiments described above.

It is a feature and advantage of the present invention to provide a cigarette saver that enables a person to extinguish a cigarette and to store it so that the person can relight the extinguished cigarette and smoke it later.

Another feature and advantage of the present invention is to provide a cigarette
15 saver that can be sold with a cigarette package.

A further feature of the present invention is to provide a cigarette saver that can be stored in a cigarette package.

A still further feature of the present invention is to provide a cigarette package that includes cigarettes and a cigarette saver that enables a smoker to extinguish a
20 lighted cigarette and store it for subsequent relighting.

Another feature of advantage of the present invention is to provide a cigarette package that includes cigarettes, a cigarette saver and a crush proof box.

With the foregoing and other advantages and features of the invention that will become hereinafter apparent, the nature of the invention may be more clearly understood by reference to the following detailed description of the invention, the appended claims and to the several views illustrated in the drawings.

5

Brief Description of the Drawings

FIG. 1 is a perspective view of an embodiment of a cigarette saver according to the present invention;

FIG. 2 is a front elevational view of an embodiment of a cigarette saver according to the present invention;

FIG. 3 is a top elevational view of an embodiment of a cigarette saver according to the present invention;

FIG. 4 is a bottom elevational view of an embodiment of a cigarette saver according to the present invention;

FIG. 5 is a side elevational view of an embodiment of a cigarette saver according to the present invention;

FIG. 6 is a cross-sectional view of the cigarette saver shown in FIG. 3 taken along the line 6-6;

FIG. 7 is a cross-sectional view of the cigarette saver shown in FIG. 2 taken along the line 7-7;

FIG. 8 is a perspective view of an embodiment of a cigarette saver according to the present invention with an extinguished cigarette;

FIG. 9 is a front elevational view of an embodiment of a cigarette saver according to the present invention with an extinguished cigarette;

FIG. 10 is a top elevational view of an embodiment of a cigarette saver according to the present invention with an extinguished cigarette;

5 FIG. 11 is a cross-sectional view of the cigarette saver shown in FIG. 10 taken along the line 11-11;

FIG. 12 is a perspective view of an embodiment of a cigarette package according to the present invention having cigarettes and a cigarette saver;

10 FIG. 13 is a front elevational view of an embodiment of a cigarette package according to the present invention having cigarettes and a cigarette saver;

FIG. 14 is a top elevational view of an embodiment of a cigarette package according to the present invention having cigarettes and a cigarette saver;

FIG. 15 is a perspective view of an embodiment of a cigarette package of the present invention showing cigarettes and a cigarette saver inside of a crush proof box;

15 FIG. 16 is a perspective view of an embodiment of a cigarette package of the present invention showing cigarettes and a cigarette saver inside of a crush proof box;

FIG. 17 is a perspective view of another embodiment of a cigarette saver of the present invention;

20 FIG. 18 is a perspective view of an embodiment of a cigarette saver of the present invention;

FIG. 19 is a top elevational view of an embodiment of a cigarette saver of the present invention;

FIG. 20 is a cross-sectional view of the cigarette saver shown in FIG. 19 taken along the line 20-20; and

FIG. 21 is a perspective view of an embodiment of a cigarette package of the present invention showing cigarettes and a cigarette saver inside of a crush proof box.

5

Detailed Description of the Invention

The present invention relates to a cigarette saver and to a package of smoking articles, such as cigarettes, having a cigarette saver. An embodiment of a cigarette package of the present invention comprises a crush proof box, a plurality of cigarettes, and a cigarette saver. In one embodiment, a cigarette saver is a device having two end portions, wherein the first end portion includes an opening to a channel.

The opening may be any shape that will assist in receiving cigarettes into the channel of the cigarette saver. Suitable openings are elliptical and round with the width of the opening being greater than the diameter of a cigarette. The channel may comprise a guide portion and an extinguishing portion. The guide portion preferably has a greater width than the extinguishing portion. The guide portion begins at the opening and may narrow to the extinguishing portion. The extinguishing portion may be substantially cylindrical with a diameter that is only slightly larger than the diameter of a cigarette to assist in extinguishing the cigarette by reducing the amount of air that enters the channel.

The length of the channel in the cigarette saver is preferably less than the length of a cigarette. The length of the channel may be such a length that when an

extinguished cigarette is in the cigarette saver, a portion of the cigarette butt extends from the opening to allow a smoker to remove and relight the cigarette. In one embodiment, the channel does not extend through the length of the cigarette saver and the end of the channel that terminates in the cigarette saver is tapered.

5 Referring now in detail to the drawings, FIGS. 1-7 illustrate an embodiment of a cigarette saver 5 of the present invention. FIG. 1 is a perspective view of an embodiment of a cigarette saver of the present invention. FIG. 2 is a front elevational view of an embodiment of a cigarette saver of the present invention. FIG. 3 is a top elevational view and FIG. 4 is a bottom elevational view of an embodiment of a cigarette saver according to the present invention. FIG. 5 is a side elevational view of an embodiment of a cigarette saver of the present invention. FIGS. 6 and 7 are cross-sectional views of a cigarette saver of the present invention. FIG. 6 is a cross-sectional view of the cigarette saver shown in FIG. 3 taken along the line 6-6 and FIG. 7 is a cross-sectional view of the cigarette saver shown in FIG. 2 taken along the line 7-7.

The cigarette saver 5 shown in FIGS. 1-7 comprises a substantially rectangular body having two end portions 10,15. The first end portion 10 includes an opening 20 to a channel 25. As shown in FIGS. 1, 3 and 6, the opening 20 may be elliptical. In other embodiments (e.g., FIGS. 18-20), the opening may be round. The width ("W") of the opening 20 is preferably greater than the diameter of cigarettes to be extinguished and saved.

The length of the channel 25 (L_c in FIG. 6) is preferably less than the length of cigarettes to be extinguished and saved. The channel 25 preferably does not extend

through the length (Ls in FIG. 5) of the cigarette saver 5. In embodiments where the channel 25 does not extend through the length (Ls in FIG. 5) of the cigarette saver 5, the end 30 of the channel 25 terminates in the cigarette saver 5. In one embodiment, the end of the channel that terminates in the cigarette saver is tapered. A tapered end of the channel assists in extinguishing the cigarette.

In the embodiment shown in FIGS. 1-7, the channel 25 comprises a guide portion 35 and an extinguishing portion 40. The guide portion 35 helps align the cigarette and guide it into the extinguishing portion 40. As shown in FIGS. 1-7, the guide portion 35 may be an elliptical funnel. Persons of ordinary skill in the art will recognize that other shapes may be used to guide the cigarette into the extinguishing portion. The diameter (D in FIG. 6) of the extinguishing portion 40 may be only slightly greater than the diameter of the cigarette to be extinguished. With a diameter of the extinguishing portion 40 that is only slightly greater than the cigarette, the cigarette is more easily extinguished as the amount of air that can enter the channel 25 is reduced.

FIGS. 8-11 illustrate an embodiment of a cigarette saver 60 of the present invention with an extinguished cigarette 70 in the channel 65. FIGS. 8, 9 and 10 show perspective, front elevational and top elevational views, respectively. FIG. 11 is a cross-sectional view of the cigarette saver shown in FIG. 10 taken along the line 11-11. The channel comprises a guide portion 80 and an extinguishing portion 75. As shown in FIGS. 8-10, the length of the channel 65 is less than the length of cigarette 70 to be extinguished. Also, the diameter of the extinguishing portion 75 is only slightly greater than the diameter of the cigarette 70 to be extinguished.

FIGS. 12-15 illustrate an embodiment of a cigarette package of the present invention. As shown, the cigarette package 100 comprises a crush proof box 105, a plurality of cigarettes 110 and a cigarette saver 115. The cigarette saver 115 may be a cigarette saver as described above with regard to FIGS. 1-11, comprising a substantially rectangular body having two end portions 140,145. The first end portion 145 includes an opening 125 to a channel. The opening 125 may be elliptical, circular or any other shape conducive to the insertion of cigarettes. The channel may comprise a guide portion 135 and an extinguishing portion 130. The guide portion 135 helps align the cigarette and guide it into the extinguishing portion 130. As shown in FIGS. 12-15, the guide portion 135 may be an elliptical funnel. Persons of ordinary skill in the art will recognize that other shapes may be used to guide the cigarette into the extinguishing portion 130.

While the embodiment of a cigarette package shown in FIGS. 12-15 comprises a crush proof box, other embodiments may comprise a soft pack instead. Typical crush proof boxes are designed to include about twenty or about twenty-five cigarettes. A cigarette package of the present invention may comprise a crush proof box designed to include twenty-five cigarettes. Using a crush proof box of this size, the crush proof box can hold twenty cigarettes and a cigarette saver as shown in FIGS. 12-15. The cigarettes 110 shown in FIGS. 12-14 are wrapped in foil 120.

Other sizes of crush proof boxes may be used, such that the number of cigarettes in the cigarette package vary. For example, FIG. 16 shows another embodiment of a cigarette package 170 of the present invention comprising a crush proof box 175 designed to include twenty-three cigarettes, a cigarette saver 180 and

twenty cigarettes 185. The lid of the crush proof box is not illustrated to better display the arrangement of the cigarettes 185 and the cigarette saver 180 inside the crush proof box 175.

FIG. 17 shows an embodiment of a cigarette saver 180 that may be included in a cigarette package of the present invention where the cigarette saver 180 and twenty cigarettes fit in a crush proof box designed to include twenty-three cigarettes as shown in FIG. 16. The cigarette saver 180 shown in FIG. 17 comprises a substantially rectangular body having two end portions 190,195. The first end portion 190 includes an opening 200 to a channel 205.

FIGS. 18-20 illustrate another embodiment of a cigarette saver 250 of the present invention. The cigarette saver 250 shown in FIGS. 18-20 comprises a substantially rectangular body having two end portions 255,260. The first end portion 255 includes an opening 265 to a channel 270. As shown in FIGS. 18 and 19, the opening 265 is round. The width ("D" in FIG. 19) of the opening 265 is preferably greater than the diameter of cigarettes to be extinguished and saved.

The length of the channel 270 ("L" in FIG. 20) is preferably less than the length of cigarettes to be extinguished and saved. The channel 270 preferably does not extend through the length of the cigarette saver 250. In embodiments where the channel 270 does not extend through the length of the cigarette saver 250, the end 272 of the channel 270 terminates in the cigarette saver 250. In one embodiment, the end of the channel that terminates in the cigarette saver is tapered. A tapered end of the channel assists in extinguishing the cigarette.

FIG. 21 is a perspective view of another embodiment of a cigarette package of the present invention. As shown, the cigarette package 272 comprises a crush proof box 275, a plurality of cigarettes 280 and a cigarette saver 250. The cigarette saver 250 shown in FIG. 21 is the cigarette saver as described above with regard to FIGS. 18-20, comprising a substantially rectangular body having two end portions 255, 260. The first end portion 255 includes a circular opening 265 to a channel 270. While the embodiment of a cigarette package shown in FIG. 21 comprises a crush proof box, other embodiments may comprise a soft pack instead. The crush proof box 275 shown in FIG. 21 is designed to hold twenty-five cigarettes. Using a crush proof box of this size, the crush proof box can hold twenty cigarettes and a cigarette saver as shown in FIGS. 21.

A cigarette saver of the present invention may be constructed from materials known to those of ordinary skill in the art. The cigarette saver should be constructed from a material that can withstand the temperatures necessary to extinguish a lighted cigarette. For example, the cigarette saver may be constructed from plastic or metal. With a substantially rectangular solid, a cigarette saver of the present invention may be formed by mechanically drilling a channel. Cigarette savers of the present invention can also be formed by injection molding.

With respect to the descriptions set forth above, optimum dimensional relationships for the parts of the invention (to include variations in size, materials, shape, form, function and manner of operation, assembly and use) are deemed readily apparent and obvious to those skilled in the art, and all equivalent relationships to

those illustrated in the drawings and described in the specification are intended to be encompassed herein.

The foregoing is considered as illustrative only of the principles of the invention. Since numerous modifications and changes will readily occur to those skilled in the art, the foregoing is not intended to limit the invention to the exact construction and operation shown and described, and all suitable modifications and equivalents falling within the scope of the appended claims are deemed within the present inventive concept.

The features of the present invention, together with the other objects of the invention, and along with the various features of novelty which characterize the invention, are pointed out with particularity in the claims annexed to and forming a part of this disclosure.

I claim: